

A347X1.3D , A547KX1.3D A347X1.3GD , A547KX1.3GD



TECHNICAL FEATURES:

- Machine body Ø460mm
- Side channel blower with three phase motor asynchronous marked ATEX EX II 3GD
- by-pass valve put in as standard
- Vacuum meter to control the filter efficiency
- Electric cable 10m long with industrial plug Ph+ earth 16A IP67 easy to disconnect from the machine
- Manual filter shaker on the side
- Star filter of polyester cat. "L" - Ø460mm, 14 pockets in antistatic version
- Quick inlet Ø70mm
- Waste bin of 100lt with handle and castors
- Hose support in the front side and accessories
- compartment
- Relief valve as standard
- Rear castors Ø200mm with brake, front castors Ø150mm, antistatic version
- Painted version with trolley Ral 9005 (black), waste bin in stainless steel and filter chamber Ral 7001 (grey)
- X2 version with bin and filter chamber in stainless steel
- X3 version completely in stainless steel, control box included
- Electric control box with phase sequence to avoid the suction unit turning in the opposite direction with consequent blowing out of the sucked dust (ONLY FOR 3D)
- Available with IE2 motors

		A347X1.3D A347X1.3D	A547KX1.3D A547X1.3GD
Tension /Voltage	Volts	230-400V/50Hz	230-400V/50Hz
Power	Kw	2,6	5,2
Depression Max	mbar max	300	290
Max working depression	mbar	220	230
Max air flow	m³/h	310	520
Primary filter surface	m²	2,55	2,55
Upstream absolute filter surface	m²	7,50	7,50
Downstream absolute filter surface	m²	7,25	7,25
Cartridge filter surface	m²	5	5
Container capacity	Lt	100	100
Product inlet	mm	Ø70	Ø70
Noise level	DbA	72	72
Overall dimension	Cm	66x125x150H	66x125x150H
Weight	Kg	125	165
Protection	IP	55	55