

A63 , A65, A103



TECHNICAL FEATURES:

- Machine body Ø460mm
- Side channel blower with three phase motor asynchronous, exposed to view on top of the filter chamber
- Electric cable 9m long with industrial plug 3 Ph+ Earth 16A
- Manual filter shaker on the side
- Star filter of polyester cat. "L" - Ø460mm
- Quick inlet Ø70mm
- For models A63 and A65 and relative versions: 65l waste bin with integrated handle and castors
- 100 l waste bin with handles and castors for model A103 and relative versions
- Rear castors Ø150mm, front castors Ø125mm with brake
- Painted version with trolley Ral 9005 (black), waste bin and filter chamber Ral 7001 (grey)
- X1 version with waste bin in stainless steel
- X2 version with waste bin and filter chamber in stainless steel
- Available with motor housing in painted version Ral7001 (grey) and in stainless steel (NOT FOR A65)
- We recommend using accessories of Ø40mm and Ø50mm
- Only available for working at 50 Hz

		A63	A65	A103
Tension / Voltage	Volts	230-400V/50Hz	230-400V/50Hz	230-400V/50Hz
Power	Kw	2.2	4	2.2
Depression max	mbar max	300	290	300
Max working depression	mbar	200	200	200
Max air flow	m ³ /h	310	520	310
Primary filter surface	m ²	1,90	1,90	1,90
Absolute filter surface	m ²	2,20	2,20	2,20
Container capacity	Lt	65	65	100
Product inlet	mm	Ø70	Ø70	Ø70
Noise level	DbA	75	77	75
Overall dimensions	Cm	64x73x162h	64x73x162h	64x73x190H
Weight	Kg	77	93	80
Protection	IP	55	55	55