

ONE63ECHOX1



TECHNICAL FEATURES:

- Machine body Ø460mm
- Single phase brush motors double stage by-pass
- Motor-head entirely made of metal white painted
- Independent switches for each motor
- Vacuum-meter and red light to control filter efficiency
- Electric cable 9m long with Schuko plug
- Manual filter shaler on top of the head
- Ø460mm star filter in antistatic polyester for high temperatures, with PTFE treatment and standard absolute filter
- Quick product inlet Ø70mm
- Waste bin of 65 l with integrated handle and castors
- Rear castors Ø150mm, front castors Ø125mm with brake
- Painted version with trolley Ral 9005 (black), waste bin and filter chamber Ral 7001 (grey)
- X1 version with waste bin in stainless steel
- We recommend using accessories of Ø40mm and Ø50mm

		ONE63ECHOH
Tension /Voltage	Volts	1Ph 230V/50-60Hz
Power	Watt	3300
Depression max	mbar	210
Max air flow	m ³ /h	510
Primary filter surface	m ²	1,90
Absolute filter surface	m ²	2,90
Container capacity	Lt	65
Product inlet	mm	Ø70
Noise level	DbA	77
Overall dimensions	Cm	78X64X135H
Weight	Kg	65
Protection	IP	43