

## A347/60 , A347 A547, A547K



**TECHNICAL FEATURES:**

- Machine body Ø460mm
- Side channel blower with three phase motor asynchronous
- Vacuum meter to control the filter efficiency
- Electric cable 10m long with industrial plug 3Ph+T 16A
- Manual filter shaker on the side
- Star filter of polyester cat. "L" - Ø460mm, 14 pockets
- Quick inlet Ø70mm
- Waste bin of 65l and 100l with integrated handles and castors
- Hose support in the front side and accessories compartment
- Rear castors Ø200mm, front castors Ø150mm with

brake

- Painted version with trolley Ral 9005 (black), waste bin and filter chamber Ral 7001 (grey)
- X1 version with waste bin in stainless steel
- X2 version with bin and filter chamber in stainless steel
- X3 version completely in stainless steel, control box included
- Electric control box with phase sequence to avoid the suction unit turning in the opposite direction with consequent blowing out of the sucked dust
- UL labelling on all electric parts, excluded for model A547K
- Available with IE2 motors
- Available in IE3 version with inverter control system

		A347/60	A347	A547	A547K
Tension /Voltage	Volts	230-400V/50Hz	230-400V/50Hz	230-400V/50HZ	230-400V/50Hz
Power	Kw	2,2	2,2	4	4
Depression Max	mbar max	300	300	460	300
Max working depression	mbar	200	200	400	200
Max air flow	m <sup>3</sup> /h	310	310	220	520
Primary filter surface	m <sup>2</sup>	2.55	2.55	2.55	2.55
Upstream absolute filter surface	m <sup>2</sup>	7,50	7,50	7,50	7,50
Downstream absolute filter surface	m <sup>2</sup>	7,25	7,25	7,25	7,25
Cartridge filter surface	m <sup>2</sup>	5	5	5	5
Container capacity	Lt	65	100	100	100
Product inlet	mm	Ø70	Ø70	Ø70	Ø70
Noise level	DbA	72	72	72	72
Overall dimension	Cm	66x125x135H	66x125x150H	66X125X150H	66X125X150H
Weight	Kg	125	130	135	165
Protection	IP	55	55	55	55