

AD46/60X1, AD46/100X1



TECHNICAL FEATURES:

- Machine body Ø460mm
- Pneumatic ejector (Venturi system)
- Star filter of polyester cat. "L" antistatic
- Manual filter shaker on top of the filter chamber
- Manometer to control the compressed air pressure
- Quick inlet Ø70mm
- Container of 65 or 100 l with handles and castors, in stainless steel for the X1 standard version
- Rear castors Ø150mm, front castors Ø125mm with brake
- Accessories compartment
- Hose for the supply of the compressed air, 10 m. long, antistatic, complete with connector
- standard X1 version with trolley Ral 9005 black, container in stainless steel and filter chamber Ral 7001 grey
- X2 version with container and filter chamber in stainless steel, trolley Ral 9005 black
- X3 version completely in stainless steel
- We recommend using accessories for cleaning of Ø50mm

		AD46/60X1	AD46/100X1
Air compressed consumption	LT/MIN	1200NI/min	1200NI/min
Power	Watt	-	-
Depression max	mbar	280	280
Max air flow	m ³ /h	400	400
Primary filter surface	m ²	1,90	1,90
Absolute filter surface (inside)	m ²	2,2	2,2
Absolute filter surface (outside)	m ²	2.8	2.8
Container capacity	Lt	65	100
Product inlet	mm	Ø70	Ø70
Noise level	DbA	72	72
Overall dimensions	Cm	68X74X135h	68X74X150H
Weight	Kg	60	62
Air compressed required	bar	4-6	4-6