

BA2205, BA2805, BA281



TECHNICAL FEATURES:

- Side channel blower with asynchronous motor, three phase or single phase, exposed to view
- C version, with motor into protective housing white painted
- Filter body Ø220 for model BA2205
- Filter body Ø280 for models BA2805, BA281
- Bag filter of polyester cat. "L", without manual filter shaker
- Straight inlet Ø40mm
- Base of support
- Standard version in painted steel RAL 9003 (white)
- X version: all in stainless steel (both filter chamber and base of support), motor exposed to view
- T version: with magneto-thermal switch into IP 55 box
- CX2 version: all in stainless steel

		BA2205	BA2805	BA281
Tension /Voltage	Volts	230-400V/50Hz	230-400V/50Hz	230-400V/50Hz
Power	Watt	0.37	0.37	0.90
Depression max	mbar	160	160	230
Max working depression	mbar	110	110	150
Max air flow	m ³ /h	80	80	150
Primary filtering surface	m ²	0.15	0.23	0.23
Absolute filtering surface	m ²	NO	1,20	1,20
Container capacity	Lt	3	9	9
Product inlet	mm	Ø40	Ø40	Ø40
Noise level	DbA	70	70	70
Overall dimensions	Cm	35X60X46H	35X60X46H	35X60X45H
Weightl	Kg	20	22	30
Protection	IP	54	54	54