

## BA3605, BA361, BA362, BA363, BA465



### TECHNICAL FEATURES:

- Side channel blower with asynchronous motor, three phase or single phase, exposed to view
- C version with motor into protective housing white painted
- Filter body Ø360
- Star filter of polyester cat. "L"
- Manual filter shaker
- Straight inlet Ø50mm
- Base of support
- Standard version in painted steel RAL 9003 (white)
- X version all in stainless steel (both filter chamber and support) and motor exposed to view
- T version : with magneto-thermal switch into IP 55 box

		BA3605	BA361	BA362	BA363	BA465
Tension /Voltage	Volts	230-400V/50Hz	230-400V/50Hz	230-400V/50Hz	230-400V/50Hz	230-400V/50Hz
Power	Watt	0.37	0.90	1.5	2.2	4
Depression max	mbar	160	230	250	310	400
Max working depression	mbar	110	150	210	200	200
Max air flow	m <sup>3</sup> /h	80	150	210	310	520
Primary filtering surface	m <sup>2</sup>	0.70	0.70	0.70	0.70	1.9
Absolute filtering surface	m <sup>2</sup>	1,20	1,20	1,20	1,20	2.9
Container capacity	Lt	12	12	12	12	25
Product inlet	mm	Ø50	Ø50	Ø50	Ø50	Ø70
Noise level	DbA	70	70	64	73	78
Overall dimensions	Cm	39X80X64H	39X80X64H	39X80X64H	39X80X64H	46X105X85H
Weightl	Kg	30	35	42	52	62
Protection	IP	54	54	55	54	54