

ONE32EP, ONE62EP



TECHNICAL FEATURES:

- Machine body Ø460mm
- Single phase brush motors double-stage by-pass
- Motor-head in sound proof ABS/metal in black colour
- Independent switches for each motor
- Vacuum-meter to control filter efficiency
- Electric cable 9m long with Schuko plug
- Manual filter shaker on top of the head
- Star filter of polyester cat. "L"- Ø460mm
- Quick product inlet Ø70mm
- Waste bin of 39 and 65 l. with integrated handle and castors
- Rear castors Ø150mm, front castors Ø125mm with brake
- Painted version with trolley RAL 9005 (black), container and filter chamber Ral 7001 (grey)
- X1 version with waste bin in stainless steel
- We recommend using accessories of Ø40mm and Ø50mm

		ONE32EP	ONE62EP
Tension/ Voltage	Volts	1Ph 230V/50-60Hz	1Ph 230V/50-60Hz
Power	Watt	2200	2200
Depression Max	mbar	210	210
Max air flow	m ³ /h	340	340
Primary filter surface	m ²	1,90	1,90
Absolute filter surface	m ²	2,2	2,2
Container capacity	Lt	39	65
Product inlet	mm	Ø70	Ø70
Noise level	DbA	77	77
Overall dimensions	Cm	72X54X128H	72X54X138H
Weight	Kg	49	51
Protection	IP	44	44