

A21_{LUS}M, A62_{LUS}M



TECHNICAL FEATURES:

- Machine body Ø360mm and Ø460mm
 - Side channel turbine with single-phase asynchronous motor
 - Vacuum gauge for indication of filter clogging level
 - 9m power cable with Schuko plug
 - Lateral manual filter shaker
 - Polyester star filter 12 pockets class “L” - Ø360mm for model A21PM
 - Polyester star filter class “L” - Ø460mm for model A62PM
 - Quick connector Ø70mm
 - 25 Lt container with integrated handle and wheels
- for A21PM model
 - 65 Lt container with integrated handle and wheels for A62PM model
 - Rear wheels Ø125mm, front wheels Ø100mm with brake
 - Painted version with frame Ral 9005 black and container and side Ral 9003 white
 - X1 version with stainless steel container
 - X2 version with stainless steel container and filter chamber
 - X3 version completely in stainless steel
 - Ideal for use with suction accessories Ø40mm

		A21PM	A62PM
Tension/ Voltage	Volts	1~ 230V/50Hz	1~ 230/50Hz
Plug	A	Schuko	Schuko
Power	kW	1.5	2.2
Depression max	mbar max	250	300
Max working depression	mbar	200	220
Max air flow	m ³ /h	200	310
Primary filter surface	m ²	1,14	1,90
Absolute filter surface	m ²	1,20	3,1
Container capacity	Lt	25	65
Product inlet	mm	Ø70	Ø70
Noise level	DbA	67	75
Overall dimensions	cm	47x61x135h	64x77x162h
Weight	Kg	60	78
Protection	IP	55	55