

ONE63ECOC



TECHNICAL FEATURES:

- Machine body Ø460mm
- 3 single phase brush motors double stage by-pass
- Head entirely made of metal black painted
- Independent switches for each motor
- Vacuum-meter and re light to control the filter efficiency
- Electric cable 9m with Schuko plug
- Kit cartridge filter Ø460 with 3 cartridges- total surface 5m²
- Automatic cleaning of the filters with compressed air jet
- Quick inlet Ø70mm
- Waste bin of 65 l with integrated handle and castors
- Rear castors Ø150mm, front castors Ø125mm with brake
- Painted version with trolley Ral 9005 (black), container and filter chamber Ral 7001 (grey)
- X1 version with waste bin in stainless steel
- Single phase compressor, power 1.5 and 24 l tank

ONE63ECOC		
Tension /Voltage	Volts	1~ 230V/50-60Hz
Plug	A	Schuko
Power	Watt	5250 (3300+1500)
Depression max	mbar	210
Max air flow	m ³ /h	510
Primary filter surface	m ²	5
Absolute filter surface	m ²	NO
Container capacity	Lt	65
Product inlet	mm	Ø70
Noise level	DbA	-
Overall dimensions	cm	70x92x150h
Weight	Kg	90
Protection	IP	43