

Via Mavore 1640/C - 41059 Zocca (MO) Italy - Tel. +39.059.986833 - Fax +39.059.9750021 info@rgsimpianti.com - www.rgsvacuumsystems.com













Three Phase industrial Vacuum Cleaners: "ECO" and "EP" series







A546KECOX2

Quality and reliability at the right price

Increased in its range of available engine powers, now from 2,2 kW to 5,5 kW and in the filtering surface, available now with 1,9 m2 and 3,4 m2, each customer can find the right solution for all his needs. Thanks to the use of side channel blowers and the total absence of mechanical parts subject to wear, this range of vacuum cleaners is particularly suitable for prolonged uses, even 24 hours a day.

A sturdy frame made in one piece, the possibility to choose between all-steel casing or in ABS, quick release of the container, the availability of many accessories and options are all part of this series of vacuum cleaners with an excellent quality/price ratio.

Extremely suitable for mechanical, construction, food processing, ceramics, rubber plastics and textiles, this range of vacuum cleaners is tailored to suit all needs of general cleaning of the environment and of the equipment or of continuous vacuuming on packaging or process machines.



Kit absolute filter HEPA H14



Kit cartridge filters



Kit LONGOPAC for the collection of the sucked materials into tubular continuous bag

These vacuum cleaners can be equipped with the wide range of RGS options to make the job of the operators light and safe:

- Absolute filter to retain even the finest dusts, with efficiency 99,995" (HEPA class H14)
- Automatic cleaning systems of the filter
- Collecting systems of the sucked material into plastic bag or into continuous bag
- Lifting systems for the container by means of a fork-lift
- Automatic stopping devices in case of vacuuming of liquids
- Discharging systems for liquids

ECO version: all-steel casing

EP version: casing in ABS and steel



Kit grill and depressor to collect the material into a plastic bag



Kit Container lifting



MODEL	A346/30EP	A346/60EP	A346EP A346ECO	A546 60KEP	A546KEP	A546KECO	A756KECO
Mot. Pow.	2,2 Kw	2,2 Kw	2,2 Kw	4 Kw	4 Kw	4 Kw	5,5 Kw
Max. vacuum	300 mbar	300 mbar	300 mbar	290 mbar	290 mbar	400 mbar	400 mbar
Vacuum	200 mbar	200 mbar	200 mbar	200 mbar	200 mbar	200 mbar	300 mbar
Air flow	310 m³/h	310 m³/h	310 m³/h	520 m³/h	520 m³/h	520 m³/h	520 m³/h







