


ONE21, ONE22, ONE22FP











TECHNICAL FEATURES:

- Machine body Ø360mm
- Single phase brush motor double stage by-pass
- Motor-head in ABS/metal black coloured
- Indipendent switches for each motor
- Vacuum-meter to chek the filter efficiency
- Electric cable 9m. long with Schuko plug
- Manual filter shaker on top of the vacuum
- Star filter in polyester cat. "L" for models ONE21 and ONE22
- Star filter in polyester cat. "M" for model ONE22FP
- Quick inlet Ø70mm (for models ONE21 and ONE22) Ø50mm (for model ONE22FP)
- Dust bin of 25 lt (for models ONE21 and ONE22) 20 lt

(for model ONE22FP) provided with handle and castors

- Rear castors Ø125mm, front castors Ø100mm with brake (for models ONE21 and ONE22)
- Rear castors Ø200mm, front castors Ø100mm with brake (for model ONE22FP)
- Painted version with trolley in Ral 9005 (black), container
- and filter chamber in Ral 7001 (grey)
- X1 version with dust bin in stainless steel
- X2 version with dust bin and filter chamber in stainless steel
- X3 version with dust bin, filter chamer and trolley in stainless steel but motor-head in painted/ABS
- We recommend using cleaning accessories Ø40mm for 1-motor versions and Ø50mm for 2-motors versions

		ONEO4	ONEGO	ONEGOED
		ONE21	ONE22	ONE22FP
Tension /Voltage	Volts	1~ 230V/50-60Hz	1~ 230V/50-60Hz	1~ 230V/50-60Hz
Plug	Α	Schuko	Schuko	Schuko
Power	Watt	1100	2200	2200
Depression max	mbar	210	210	210
Max air flow	m³/h	170	340	340
Primary filtering surface	m²	0,70	0,70	0,70
Absolute filtering surface	m²	1,20	1,20	1,20
Container capacity	Lt	25	25	20
Product inlet	mm	Ø70	Ø70	Ø50
Noise level	dB(A)	76	78	78
Overall dimensions	cm	48x63x104h	48x63x104h	49x49x102h
Weight	Kg	30	32	23
Protection	IP	44	44	44