

ONE82WD, ONE82WPX1



TECHNICAL FEATURES:

- Machine body Ø460mm
- 2 single phase brush motors double stage by-pass
- Head entirely made of metal black painted
- Independent switches for each motor
- Vacuum-meter and red light to control filter efficiency
- Electric cable 9m with Schuko plug
- Model WD: bag filter of polyester for dust, nylon filter,
- Float for liquids and discharge hose Ø30x1.5m with cap
- Model WP: nylon filter, float for liquids, water pump and discharge hose Ø30x3m with manual valve
- Quick inlet Ø70mm
- Container with 80 l. capacity with handles and castors
- Rear castors Ø200mm, front castors Ø100mm with brake
- Model WD: painted version with trolley Ral 9005 (black) filter chamber Ral 7001 (grey) and X1 version with container in stainless steel
- Model WP: container in stainless steel and trolley black painted Ral 9005

		ONE82WD	ONE82WPX1
Tension/Voltage	Volts	1~ 230V/50-60Hz	1~ 230V/50-60Hz
Plug	A	Schuko	Schuko
Power	Watt	2200	2200
Depression max	mbar	210	210
Max air flow	m ³ /h	340	340
Primary filter surface	m ²	0,58	-
Absolute filter surface	m ²	-	-
Container capacity	Lt	85	85
Product inlet	mm	Ø70	Ø70
Noice level	DbA	76	76
Overall dimensions	cm	55x60x126h	55x60x126h
Weight	Kg	30	30
Protection	IP	44	44