

A1056, A1056K



TECHNICAL FEATURES:

- Side channel blower with three phase motor asynchronous put in the back side of the vacuum cleaner into protective housing
- Electric cable 10m long with industrial plug 3Ph+T 32A that can be disconnected from the vacuum cleaner
- Star filter Ø560 with big surface
- Manual filter shaker on top of the filter chamber
- Vacuum gauge to monitor the filter efficiency
- By-pass relief valve put in as standard
- Waste bin of 175l with castors and side handles for the emptying and as an option with lifting system for fork lift
- Quick inlet Ø100
- Fixed wheels Ø200 and revolving wheels Ø200 with brake on bearings to grant high manoeuvrability
- Painted version with frame RAL 9005 (black) and machine Ral 7001 (grey)
- X1 version with waste bin in stainless steel
- X2 version with container and filter chamber in stainless steel
- X3 version all in stainless steel
- Electric switchboard with soft-start and PLC to control the motor, already configured for remote control

		A1056	A1056K
Tension/Voltage	Volts	3~ 400V/50Hz *	3~ 400V/50Hz *
Plug	A	3P + T 32A	3P + T 32A
Power	Kw	7.5	7.5
Depression max	mbar max	520	350
Max working depression	mbar	400	225
Max air flow	m³/h	540	820
Primary filter surface	m²	3,4 -Ø560	3,4 -Ø560
Upstream absolute filter	m²	NO	NO
Downstream absolute filter	m²	7,25	18
Cartridge filter surface	m²	10	10
Container capacity	Lt	175	175
Product inlet	mm	Ø100	Ø100
Noise level	DbA	74	78
Overall dimensions	cm	74x157x187h	74x157x187h
Weight	Kg	375	300
Protection	IP	55	55

* other voltages and frequencies available on request