

A346/30EP, A346/60EP, A546/30KEP, A546/60KEP



TECHNICAL FEATURES:

- Side channel blower with three phase motor asynchronous placed in the back side into a protective housing with ABS cover
- Electric cable 10m long with industrial plug 3Ph+T 16A
- Star filter Ø460 cat. "L" with big filtering surface
- manual filter shaker on top of the filter chamber
- Vacuum-meter to control the filter efficiency
- Waste bins of 39 and 65 lt easily removable with integrated handle and wheels
- Quick inlet Ø70 for easy attachment of accessories
- Accessories compartment and support for the flex. hose in the front side
- Support cable reeler in the back side
- Painted version in Ral 7001 grey
- X1 version with waste bin in stainless steel
- Fixed wheels Ø150mm and revolving wheels with brake Ø125mm

		A346/30EP	A346/60EP	A546/30KEP	A546/60KEP
Tension /Voltage	Volts	3~ 230-400V/50Hz	3~ 230-400V/50Hz	3~ 400V/50Hz *	3~ 400V/50Hz *
Plug	A	3P + T 16A	3P + T 16A	3P + T 16A	3P + T 16A
Power	kW	2.2	2.2	4	4
Depression Max	mbar max	300	300	300	300
Working depression	mbar	200	200	250	250
Max air flow	m ³ /h	310	310	410	410
Primary filter surface	m ²	1,90	1,90	1,90	1,90
Upstream absolute filter surface	m ²	3,1	3,1	3,1	3,1
Downstream absolute filter surface	m ²	NO	NO	NO	NO
Cartridge filter surface	m ²	5	5	5	5
Container capacity	Lt	39	65	39	65
Product inlet	mm	Ø70	Ø70	Ø70	Ø70
Noise level	DbA	74	74	74	74
Overall dimensions	cm	64x112x121h	64x112x135h	64x112x121h	64x112x135h
Weight	Kg	115	115	142	142
Protection	IP	55	55	55	55

* other voltages and frequencies available on request