

## A346/30EPX1.3D, A346/60EPX1.3D, A546/30KEPX1.3D, A546/60KEPX1.3D



### TECHNICAL FEATURES:

- Side channel blower with three phase motor asynchronous marked ATEX EX II 3D put into a protective housing in the back side of the vacuum cleaner, with carter in ABS
- Electric cable 10m long with industrial plug 3Ph+earth 16A - IP 67
- Star filter in polyester "L" antistatic
- Manual filter shaker on top of the filter chamber for the filter cleaning
- Relief valve put in as standard
- Easy-to-remove 39lt and 65lt containers with integrated handle and wheels
- Quick inlet Ø70
- Accessories compartment and support for the flex hose in the front side
- Support cable reeler in the back side
- Standard version with container in stainless steel, filter chamber and frame painted Ral 7001 grey
- Fixed wheels Ø150mm and revolving wheels with brake Ø125mm

		A346/30EPX1.3D	A346/60EPX1.3D	A546/30KEPX1.3D	A546/60KEPX1.3D
Tension /Voltage	Volts	3~ 230-400V/50Hz	3~ 230-400V/50Hz	3~ 400V/50Hz	3~ 400V/50Hz
Plug	A	3P + T 16A IP67	3P + T 16A IP67	3P + T 16A IP67	3P + T 16A IP67
Power	kW	2.2	2.2	4	4
Depression Max	mbar max	300	300	300	300
Max working depression	mbar	200	200	250	250
Max air flow	m <sup>3</sup> /h	310	310	410	410
Primary filter surface	m <sup>2</sup>	1,90	1,90	1,90	1,90
Upstream absolute filter surface	m <sup>2</sup>	3.1	3.1	3.1	3.1
Downstream absolute filter surface	m <sup>2</sup>	NO	NO	NO	NO
Cartridge filter surface	m <sup>2</sup>	5	5	5	5
Container capacity	Lt	39	65	39	65
Product inlet	mm	Ø70	Ø70	Ø70	Ø70
Noise level	DbA	74	74	74	74
Overall dimensions	cm	64X112X121h	64X112X135h	64X112X121h	64X112X135h
Weight	Kg	115	115	142	142
Protection	IP	55	55	55	55
EX Marking	EX	II3D T135 °C	II3D T135 °C	II3D T135 °C	II3D T135 °C