

A346ECO, A546KECO, A546ECO



TECHNICAL FEATURES:

- Side channel blower with three phase motor asynchronous, placed into a protective housing in the back side of the vacuum cleaner
- Electric cable 10m long with industrial plug 3Ph+T 16A for A346ECO, A546KECO and A546ECO models
- Star filter Ø460 with big surface
- Vacuum-meter to control the filter efficiency
- Electric filter shaker for cleaning the filter
- Waste bin of 100l on castors with side handles and as option a clamp to have it up with the fork lift
- Quick inlet Ø70 for easy attachment of accessories
- Painted version Ral 7001 (grey)
- X1 version with waste bin in stainless steel
- Fixed wheels Ø150mm and revolving wheels with brake Ø125mm

		A346ECO	A546KECO	A546ECO
Tension/voltage	Volts	3~ 230-400V/50Hz	3~ 400V/50Hz *	3~ 400V/50Hz *
Plug	A	3P + T 16A	3P + T 16A	3P + T 16A
Power	kW	2.2	4	4
Depression max	mbar	300	280	450
Max working depression	mbar	200	200	360
Max air flow	m ³ /h	310	540	310
Primary filter surface	m ²	1,90	1,90	1,90
Upstream absolute filter surface	m ²	3,1	3,1	3,1
Container capacity	Lt	100	100	100
Product inlet	mm	Ø70	Ø70	Ø70
Noise level	DbA	74	76	76
Overall dimensions	cm	64x113x123h	65x110x152h	65x110x152h
Weight	Kg	115	135	135
Protection	IP	55	54	55

* other voltages and frequencies available on request