

A62PX1.3GD



TECHNICAL FEATURES:

- Machine body Ø460mm
- Side channel blower with single phase motor asynchronous marked ATEX EX II 3GD
- Electric cable 10m long with industrial plug 3 Ph+ earth 16A IP67
- Manual filter shaker on side
- Star filter of polyester cat. "L" antistatic
- Quick inlet Ø70mm
- Container of 65 lt with handle and castors, in stainless steel
- Relief valve put in as standard
- Rear wheels Ø150mm, front wheels Ø125mm with brak, antistatic
- standard version with trolley Ral 9005 black, container in stainless steel and filter chamber Ral 7001 grey
- X2 version with container and filter chamber in stainless steel
- We recommend the use of suction accessories Ø40mm e Ø50mm

A62PX1.3GD		
Tension / Voltage	Volts	3~230-400V/50Hz
Plug	A	3P + T 16A IP67
Power	kW	2,6
Depression max	mbar max	300
Max working depression	mbar	220
Max air flow	m ³ /h	320
Primary filter surface	m ²	1,90
Absolute filter surface	m ²	2,20
Container capacity	Lt	65
Product inlet	mm	Ø70
Noise level	DbA	75
Overall dimensions	Cm	64X77X162h
Weight	Kg	77
Protection	IP	65
Ex Marking	EX	II 3G T4 II3D T135 °C