


A746KECO, A746ECO, A1046KECO, A1046ECO



TECHNICAL FEATURES:

- Side channel blower with three phase motor asynchronous, placed into a protective housing in the back side of the vacuum cleaner
- Electric cable 10m long with industrial plug 3Ph+T 32A
- Star filter cat. "L" Ø460 with big surface
- Vacuum-meter to control the filter efficiency
- Manual side filter shaker for filter cleaning
- Waste bin of 100l on castors with side handles and as option a clamp to have it up with the fork lift
- Quick inlet Ø70 for easy attachment of accessories
- Painted version Ral 7001 (grey)
- X1 version with waste bin in stainless steel
- Fixed wheels Ø150mm and revolving wheels with brake Ø125mm

		A746KECO	A746ECO	A1046KECO	A1046ECO
Tension/voltage	Volts	3~ 400V/50Hz *	3~ 400V/50Hz *	3~ 400V/50Hz *	3~ 400V/50Hz *
Plug	A	3P + T 32A	3P + T 32A	3P + T 32A	3P + T 32A
Power	kW	5.5	5.5	7.5	7.5
Depression max	mbar	330	470	280	350
Max working depression	mbar	300	450	260	320
Max air flow	m ³ /h	540	320	700	520
Primary filter surface	m ²	2,55	2,55	2,55	2,55
Upstream absolute filter surface	m ²	3,1	3,1	7,5	7,5
Container capacity	Lt	100	100	100	100
Product inlet	mm	Ø70	Ø70	Ø100	Ø100
Noise level	DbA	73	73	76	76
Overall dimensions	cm	65x120x175h	65x120x175h	65x120x175h	65x120x175h
Weight	Kg	170	170	170	170
Protection	IP	55	55	54	54

* other voltages and frequencies available on request