

## AS146, AS1546, AS246



### TECHNICAL FEATURES:

- Side channel blower with asynchronous motor three phase or single phase as option, placed at the bottom, under the container
- Machine body Ø460mm
- Electric cable 10m long with industrial plug 3Ph + earth 16A
- Nylon filter 200 micron
- Inspection window on the cover to check the filter bag
- Straight inlet Ø70
- Container of 105 l
- Wheels Ø63mm with brake
- Painted version RAL 9003 (white)
- X version in stainless steel

		AS146	AS1546	AS246
Tension/ Voltage	Volts	3~ 230-400V/50Hz	3~ 230-400V/50Hz	3~ 230-400V/50Hz
Plug	A	3P + T 16A	3P + T 16A	3P + T 16A
Power	kW	0.85	1.3	1.5
Depression max	mbar max	230	230	230
Max working depression	mbar	150	175	210
Max air flow	m <sup>3</sup> /h	150	150	210
Primary filter surface	m <sup>2</sup>	NO	NO	NO
Upstream absolute filter	m <sup>2</sup>	NO	NO	NO
Downstream absolute filter	m <sup>2</sup>	1,3	1,3	1,3
Cartridge filter surface	m <sup>2</sup>	NO	NO	NO
Container capacity	Lt	105	105	105
Product inlet	mm	Ø70	Ø70	Ø70
Noise level	DbA	70	70	64
Overall dimensions	Cm	Ø46x116h	Ø46x116h	Ø46x116h
Weight	Kg	42	42	55
Protection	IP	54	54	55