

ONE1030IL



TECHNICAL FEATURES:

- Machine body Ø460mm
- 3 single-phase by-pass two-stage brush motors
- Motor head in painted black metal
- Independent switches for each motor
- Vacuum gauge and red light for filter clogging indication
- Oil strainer with discharge valve in the container
- Visual tank filling indicator
- Maximum level sensor for liquids with automatic shut-off
- Discharge valve for liquids
- Electric cable 9m with Schuko plug
- Quick inlet Ø70mm
- Oil mist filter
- 100liter container for liquids
- Release container on wheels
- Rear castors Ø150mm, front castors Ø125mm with brake
- Painted version with frame Ral 9005 (black) containers both for liquids and shaving Ral 7001 (grey)
- **Including sucking accessories Ø50mm, kit K.AC.046:**
 - n.1 reduction Ø70/50 code 65042
 - 3 mt of polyurethane pipe code 35.134.1
 - 3 mt of polyurethane pipe code 35.134.1
 - n.1 rubber cone, oilproof code 65053
 - n.1 fitting junction code 65047

ONE1030IL		
Tension/Voltage	Volts	1~ 230-400V/50Hz
Plug	A	Schuko
Power	KW	3.3
Depression max	mbar max	210
Max working depression	mbar	210
Max air flow	m³/h	510
Container capacity for liquids	Lt	100
Container capacity for chips	Lt	40
Product inlet	mm	Ø70
Noise level	DbA	75
Overall dimensions	cm	78x64x120h
Weight	Kg	62
Protection	IP	44