

## A1856KX1.3D



### TECHNICAL FEATURES:

- Side channel blower with three phase motor asynchronous, put into a protective housing in the back side of the vacuum cleaner, marked EX II 3D
- Electric cable 10m long with industrial plug 3Ph+earth 32A IP 67 that can be disconnected from the machine
- Star filter Ø560 with big filtering antistatic surface
- Manual filter shaker on top of the filter chamber
- Vacuum gauge to monitor the filter efficiency
- Relief valve put in as standard
- Container of 175l on castors with side handles for the emptying and as an option the kit lifting system to have it up with a fork lift
- Quick inlet Ø100 for the quick inlet of accessories
- Fixed wheels Ø200 and revolving wheels Ø200 with brake on bearings to grant high manoeuvrability, antistatic
- Standard X1 version with black trolley, machine Ral 7001 grey and container in stainless steel
- X2 version with container and filter chamber in stainless steel
- X3 version all in stainless steel
- Electric switchboard with soft-start to control the motor, already configured for remote control

		A1856KX1.3D
Tension/Voltage	Volts	3~400-690V/50Hz
Plug	A	3P + T 32A IP67
Power	kW	12.5
Depression max	mbar max	350
Max working depression	mbar	290
Max air flow	m <sup>3</sup> /h	1050
Primary filter surface	m <sup>2</sup>	3,4 -Ø560
Upstream absolute filter	m <sup>2</sup>	NO
Downstream absolute filter	m <sup>2</sup>	18
Cartridge filter surface	m <sup>2</sup>	10
Container capacity	Lt	175
Product inlet	mm	Ø100
Noise level	DbA	75
Overall dimensions	Cm	74X157X187h
Weight	Kg	330
Protection	IP	55
EX Marking	EX	II3D T125°C