

A336



TECHNICAL FEATURES:

- Side channel blower with three phase asynchronous motor, put into a housing
- Electric cable 10m long with industrial plug 3Ph+ T 16A
- Vacuum meter to check the filter efficiency
- Machine body Ø460mm
- Manual filter shaker on top
- Star filter in polyester cat.“L”
- Quick inlet Ø70mm
- 48 l. dust bin with handles, removable
- Rear castors Ø125mm, front castors Ø100mm with brake
- Painted version with frame, waste bin and filter chamber Ral 9003 (white)
- X1 version with waste bin instainless steel
- X2 version with waste bin and container in stainless steel
- X3 version with waste bin, filter chamber and fram in stainless steel

A336

Tension / Voltage	Volts	3~ 230-400V/50Hz
Plug	A	3P + T 16A
Power	Kw	2.2
Max depression	mbar max	310
Max working depression	mbar	200
Max air Flow	m ³ /h	310
Primary filter surface	m ²	1,90
Upstream absolute filter	m ²	3,1
Downstream absolute filter	m ²	4,8
Cartridge filter kit	m ²	5
Container capacity	Lt	48
Product inlet	mm	Ø70
Noise level	DbA	69
Overall dimensions	Cm	50x80x154h
Weight	Kg	120
Protection	IP	55