

AD36X1



TECHNICAL FEATURES:

- Machine body Ø360mm
- Pneumatic ejector (Venturi system)
- Star filter of polyester cat. "L" antistatic
- Manual filter shaker on the side
- Manometer to control the compressed air pressure
- Quick inlet Ø70mm
- Container of 25 l with integrated handle and castors, in stainless steel in X1 standard version
- Rear castors Ø125mm, front castors Ø100mm with brake, antistatic
- Compressed air hose, antistatic, 10 m. long, with connector
- Standard version with trolley Ral 9005 black, container in stainless steel and filter chamber Ral 9003 white
- X2 version with trolley Ral 9005 black, container and filter chamber in stainless steel
- X3 version completely in stainless steel
- We recommend using accessories for cleaning Ø40 mm

AD36X1		
Air consumption	LT/MIN	1200NI/min
Power	Watt	-
Depression max	mbar	280
Max air flow	m ³ /h	350
Primary filter surface	m ²	0,70
Absolute filter surface	m ²	1,1
Container capacity	Lt	25
Product inlet	mm	Ø70
Noise level	DbA	70
Overall dimensions	Cm	48X65X118h
Weight	Kg	36
Compressed air required	bar	4-8
EX Marking	EX	II3G T6 II2D T85 °C