

F340X1.3D, F340X1.3GD



TECHNICAL FEATURES:

- Side channel blower with three phase asynchronous motor, placed into protective housing marked ATEX EX II 3D, EX II 3GD
- Electric cable 10m long with industrial plug 3Ph+ earth 16A IP 67
- Vacuum-meter to monitor the filter efficiency
- Machine body Ø460mm
- Manual filter shaker on top
- Star filter of polyester cat. "L" antistatic
- Quick inlet Ø70mm
- Relief valve put in as standard
- Dust bin of 48 l. with handles, removable, in stainless steel
- Rear castors Ø125mm, front castors Ø100mm with brake, antistatic
- standard version with trolley and filter chamber Ral 9003 white, container in stainless steel
- X2 version with container and filter chamber in stainless steel
- X3 version with container, filter chamber and trolley in stainless steel
- Easy installation of options and accessories

		F340X1.3D	F340X1.3GD
Tension / Voltage	Volts	3~230-400V/50Hz	3~230-400V/50Hz
Plug	A	3P + T 16A IP67	3P + T 16A IP67
Power	Kw	2.6	2.6
Max depression	mbar max	300	300
Max working depression	mbar	220	220
Max air Flow	m ³ /h	310	310
Primary filter surface	m ²	1,90	1,90
Upstream absolute filter	m ²	2,2	2,2
Downstream absolute filter	m ²	4,8	4,8
Cartridge filter kit	m ²	5	5
Container capacity	Lt	48	48
Product inlet	mm	Ø70	Ø70
Noise level	DbA	73	73
Overall dimensions	Cm	50X80X154h	50X80X154h
Weight	Kg	120	120
Protection	IP	55	55
EX Marking	EX	II3D T125 °C	II3G T3 II3D T125 °C