

A32FLPX1.3D, A174FLPX1.3D



*** VERSION WITH MOUNTED ARM
(OPTIONAL)**

TECHNICAL FEATURES:

- Machine body Ø560mm
- Fan with three-phase asynchronous motor
- Power cable 9mt with industrial plug 3 Ph+ T 16A IP67
- Side manual filter shaker
- Star filter in polyester class "L" - Ø560mm
- Inlet Ø150mm
- Container Ø560mm with various capacity with integrated handle and wheels
- Rear wheels Ø150mm, front wheels Ø125mm with brake, antistatic
- Standard version with painted version with frame Ral 9005 black and container and side Ral 7001 grey
- Optional vacuum arm kit

		A32FLPX1.3D	A174FLPX1.3D
Tension / Voltage	Volts	3~ 230-400V/50Hz	3~ 230-400V/50Hz
Plug	A	3P + T 16A IP67	3P + T 16A IP67
Power	kW	2.2	4
Depression max	mbar max	35	45
Max working depression	mbar	35	45
Max air flow	m ³ /h	1500	2500
Primary filter surface	m ²	4,2	3,2
Absolute filter surface	m ²	20	20
Container capacity	Lt	39	175
Product inlet	mm	Ø150	Ø150
Noise level	DbA	79	79
Overall dimensions	cm	65x90x185h	73x125x240h
Weight	Kg	92	235
Protection	IP	55	55
EX Marking	EX	II3D	II3D